

Robust™ Flislim - Hvit

Batch number see side sack print

Declaration of performance

Labelling of declaration of performance and clear identification code of the product type
110336-01-EN12004-C2-TE-S1

Intended use

Highly flexible thin-bed adhesive with extremely high adhesive strength. For light and natural stone that is not susceptible to discoloration. For walls and floors, indoors and outdoors.

Manufacturer

Steinhardt AS • Postboks 8627 Ranheim • 7452 Trondheim, Norway

System for assessment and verification of constancy of performance

System 4 in case of reaction to fire and System 3 for the other essential characteristics

Notified testing body

Materialprüfungsamt Nordrhein-Westfalen e.V. (MPA NRW) – Kennnummer 0432

has carried out the initial test of the product with regard to the essential characteristics (except reaction to fire) of system 3 and issued the following:

Harmonised standard

EN 12004 :2012

Declared performance

| Essential characteristics | Performance |
|---|---|
| Reaction to fire | E |
| Bond strength | Tensile adhesion strength after dry storage $\geq 1,00$ N/mm ² |
| Durability against exposure to climate/heat storage | Tensile adhesion strength after warm storage $\geq 1,00$ N/mm ² |
| Durability against exposure to climate/heat storage | Tensile adhesion strength after water storage $\geq 1,00$ N/mm ² |
| Durability against exposure to freeze/thaw storage | Tensile adhesion strength after freeze/thaw storage $\geq 1,00$ N/mm ² |
| Release of dangerous substances | NPD |

The performance of the product conforms with the declared performance. The manufacturer is solely responsible for compiling this declaration of performance which is consistent with the regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer of:



Stian Schevig, Daglig leder, Steinhardt AS.
Date of issue. 01.06.2016.