

Version: 04/2024



product description		XXL LONG
Bevel	-	2
Oak facing thickness (+0/-0,1)	mm	0,6
Class of use	ISO 10874	23 (heavy domestic use) 33 (heavy commercial use)
Residential use guarantee	-	20 years
Total thickness (tol +0/-0,1)	mm	10
Total weight	kg / m ²	8,5
Format	mm	210 x 2210
Pack content	sqm	2,7846
Pallet content	sqm	40 packs / 110,9
Pallet size	mm	L 2220 x l 960 x h 800

tests results

Intermediate layer / backing	-	HDF (860kg/m ³)
Moisture level	-	7 - 10%
Installation system	-	BestLoc X-Treme, no glue, no tools or glue-down installation
Surface treatment	-	Ultimtec high performance varnish
Resistance to abrasion	XP B 53-669	+ 15 000 Tour (TT CS10)
Gloss level	Gloss 60	5 - 7 (extra matt)
Compatibility with underfloor heating	-	PRE compatible (maxi 90 W/m ²) and low temperature hot water (see conditions)
Thermal resistance	m ² .K/W	0,052
Fire resistance	EN 13 501-1 (chêne)	Cfl-s1
CE marking	EN 14354	CE
Formaldehyde emissions	EN 717-1	E1
Formaldehyde emissions	ISO 16 000-9	M1 / A+
Environmental programme	Certification	PEFC 10-31-1047